

Amendments to the Claims

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-21. (cancelled)

22. (previously presented) A control method for selecting valve actuating modes in a multi-valve engine having at least an electromechanically actuated valve, the method comprising:

determining an operating condition of said electromechanically actuated valve;

operating the engine in at least a first and second cylinder configuration when said operating condition indicates acceptable performance of said electromechanical valve, said first configuration including engine operation where at least said valve operates and said second configuration including engine operation where at least said valve is deactivated; and

restricting operation in said first configuration and operating the engine at least in said second configuration, when said operating condition indicates a condition of degraded performance of said electromechanical valve.

23. (original) The method of Claim 22 wherein said operating condition is a temperature of said electromechanical valve actuator.

24. (original) The method of Claim 22 wherein said operating condition is an amount of electrical current flowing through said electromechanical valve.

Page 2 – AMENDMENT

Serial No. 10/805,611; Record ID 81100237

25. (original) The method of Claim 22 wherein said operating condition is a voltage drop across said electromechanical valve.

26. (original) The method of Claim 22 wherein said operating condition is a position of said electromechanical valve.

27. (original) The method of Claim 22 wherein said operating condition is an impedance of said electromechanical valve.

28-34. (cancelled)

35. (previously presented) A control method for selecting valve actuating modes in a multi-valve engine having at least an electromechanically actuated valve, the method comprising:

determining an operating condition of said electromechanically actuated valve; and

operating the engine in at least a first and second cylinder mode when said operating condition indicates acceptable performance of said electromechanical valve, said first mode including engine operation where at least said valve operates and said second mode including engine operation where at least said valve is deactivated; and

continuing operation of the engine in said second mode when said operating condition indicates a condition of degraded performance of said electromechanical valve.

36. (previously presented) The method of Claim 35 wherein said operating condition is a temperature of said electromechanical valve actuator.

Page 3 – AMENDMENT

Serial No. 10/805,611; Record ID 81100237

37. (previously presented) The method of Claim 35 wherein said operating condition is an amount of electrical current flowing through said electromechanical valve.

38. (previously presented) The method of Claim 35 wherein said operating condition is a voltage drop across said electromechanical valve.

39. (previously presented) The method of Claim 35 wherein said operating condition is a position of said electromechanical valve.

40. (previously presented) The method of Claim 35 wherein said operating condition is an impedance of said electromechanical valve.

41. (currently amended) A control method for selecting valve actuating modes in a multi-valve engine having at least ~~and~~ an electrically actuated valve, the method comprising:

determining and operating condition of said electrically actuated valve;

operating the engine in a first and second cylinder configuration when said operating condition indicates acceptable performance of said electrically actuated valve, said first configuration including operating the engine with a first number of operating cylinders, and said second ~~mode~~ configuration including a second number of operating cylinders, said second number of cylinders less than said first number of cylinders, said electrically actuated valve operating in said first ~~mode~~ configuration, said electrically actuated valve scheduled to be operating or deactivated in said second ~~mode~~ configuration; and

Page 4 – AMENDMENT

Serial No. 10/805,611; Record ID 81100237

continuing operation of the engine in said second ~~mode~~ configuration when said operating condition indicates a condition of degraded performance of said ~~electromechanical~~ electrically actuated valve.

42. (currently amended) The method of Claim 41 wherein said operating condition is a temperature of said ~~electromechanical valve actuator~~ electrically actuated valve.

43. (currently amended) The method of Claim 41 wherein said operating condition is an amount of electrical current flowing through said ~~electromechanical~~ electrically actuated valve.

44. (currently amended) The method of Claim 41 wherein said operating condition is a voltage drop across said ~~electromechanical~~ electrically actuated valve.

45. (currently amended) The method of Claim 41 wherein said operating condition is a position of said ~~electromechanical~~ electrically actuated valve.

46. (currently amended) The method of Claim 41 wherein said operating condition is an impedance of said ~~electromechanical~~ electrically actuated valve.

47. (cancelled)